

Equipment Name & Description

Zipper ZI-STB16T 630w Pillar Drill

Person Responsible

Name..... Signed.....

Date.....

Record of Service & Portable Appliance Testing (PAT)

Date	Description of action taken
3 Mar 2021	Purchased new from scheppach-direct

Zipper ZI-STB16T 630w Pillar Drill

Permitted Users – Must read the rules and sign

User Name/Signature I have read and understand all of the safety instructions	Manager Name/ Signature The user has read and understood the safety instructions
Chris Compton	Chris Compton

GENERAL SAFETY INSTRUCTIONS

The Pillar Drill must only be used for its intended purpose!

To use the Pillar Drill properly you must also observe and follow all safety regulations, the assembly instructions, operating, and maintenance instructions specified in this manual.

Everyone who uses and services the Pillar Drill have to be read and understand this manual and the Safety Regulations in force in your area.

- The Pillar Drill can be used for drilling in wood, plastic and metal with a maximum drill bit size of 16mm. Never use a damaged drill bit!
- Never use the Pillar Drill with defective or missing safety guards!
- The removal or modification of the safety equipment may result in damage to equipment and serious injury!
- The Pillar Drill must be disconnected from the power supply before opening the belt cover or spindle guard.
- Keep your work area dry and tidy! An untidy work area may cause accidents. Avoid slippery floor.
- Make sure the work area is illuminated sufficiently.
- Do not overload the Pillar Drill.
- Only one person shall operate the Pillar Drill.
- The Pillar Drill must be operated only by trained persons.
- Make sure there is nobody close to the Pillar Drill. The minimum safety distance is 2 m.
- Wear suitable work clothes! Do not wear loose clothing or jewellery as they might be caught and cause severe accidents!
- Wear a hair net if you have long hair.
- Loose objects can become entangled and cause serious injuries!
- Use personal protective equipment. Always wear eye protection. Protective equipment such as dust mask, non-skid safety shoes, hard hat, or hearing protection used for appropriate conditions will reduce personal injuries.
- Never operate with gloves on.
- Never leave the Pillar Drill running unattended! Before leaving the working area switch the Pillar Drill off and wait until the Pillar Drill stops rotating.
- Always disconnect the Pillar Drill prior to any actions performed at the Pillar Drill.
- Before starting the Pillar Drill remove chuck key from the chuck and place it in its holder.
- Use a clamping vice to secure the workpiece.
- Do not hold small workpieces with your hands, rotating parts can cause severe cut injuries.

- Keep the drill bits sharp and clean, so they get stuck less often and are easier to guide.
- Any repairs must only be carried out by the authorized service agent.